

OUTBACK



AG SUPER WASH PRODUCT INFORMATION

Description/Application

The Australian agricultural industry works with the beauty and harshness of nature. Understanding the environments your machinery is asked to perform in, helped us create a unique cleaning agent that cuts through the mud, dust, grease and hydraulic fluid that covers your equipment in the field. AG Wash was developed by a farmer with the environment in mind, so its safe for you, the land, and your equipment.

AG Wash has been specially formulated to dissolve grease, grime and dirt from farming equipment and it does that quickly and efficiently without using dangerous chemicals or damaging equipment. AG Wash is made with an acid-free, environmentally sustainable solution that can be used safely on a wide range of surfaces from painted surfaces, plastic to polished aluminium.

Benefits

- Water-based
- 100% Environmentally Friendly (Acid-free Petro-chemical free detergent)
Removed dirt stains easily and quickly
- \$\$\$ Value for money – diluted to 20:1 ratio for as little as 81 cents per litre.
- One Product for multiple surfaces – paintwork, rims, tyres, glass, polished aluminium or acrylic windows
- Environmentally sustainable, acid-free solution
- Can be safely used on a farming equipment, shed floors/walls, trucks, utes and other farming machinery
- Removes dirt stains easily and quickly
- Perfect for large-scale farming equipment

Directions for use

1. Dilute as per recommended dilution rate on the Product label.
2. Spray, brush or snow foam onto the surface being cleaned until it is saturated.
3. Agitate solution onto the surface being cleaned with a stiff-bristled brush, Broom or microfibre cloth.
4. Allow approximately 5 minutes dwell time to enable the AG Super Wash to penetrate the dirty surface.
5. Agitate the surface again lightly.
6. Rinse with a high-pressure washer or hose until all solution, and Red Dirt has been removed from the surface.

Health & Safety

Prolonged use wear gloves. Avoid contact with eyes. First Aid: if swallowed, DO NOT induce vomiting. Give a glass of water and seek medical attention. Contact Poisons Information Centre

(Ph. 13 11 26 from anywhere in Australia) or contact doctor at once. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons information Centre or a doctor. Or at least 15 minutes.



HAZARD STATEMENTS: H315 Causes skin irritation. H318 Causes serious eye irritation. H401 Toxic to aquatic life.

Please see Safety data sheet for additional information*

Packaging

Product	Code
5L Outback AG Super Wash	OC03.5
20L Outback AG Super Wash	OC03.20



Scan for SDS



www.outbackcleaningproducts.com.au

SHIELD CHEMICALS
The smart solution

Outback Cleaning Products
22 Nuttwood Cr Kununurra WA 6743
sales@outbackcleaningproducts.com.au
M: 0408486507
ABN (29 643 512 949)

OUTBACK



AG SUPER WASH PRODUCT INSTRUCTIONS

Note: If your car/ truck has previously been acid washed or cut and polished, the red stain will be harder to remove. It may require additional effort and a different application method. When cutting back the paint using an abrasive cleaning compound/ acid, sometimes etching may occur on the surface, and the paintwork ends up with microscopic ridges. The red dirt gets trapped in these ridges, making them harder to remove.

We recommend that you try the product on a small section of the surface to be cleaned to see which application method will be required.

Application method 1 Everyday wash

1. Wash off loose dirt on the surface that require cleaning.
2. Mix AG Super Wash to required dilution rate in a bucket.
3. Use a sponge Microfiber cloth or a white non-scratch scourer to wash all the surface of the vehicle,
4. Rinse of as you go with a hose or small pressure cleaner.
5. If the product dries out as you are cleaning, you will need to add water and agitate the surface to get the best result
6. Rinse then Chamois dry

Application Method 2 industrial use on large surface areas, Trucks, earth moving equipment

1. Wash large deposits of dirt off the item being cleaned.
2. Mix AG Super Wash to required dilution rate in a bucket.
3. Apply the AG Super Wash using a Snow foamer, pump up spray bottle or Pressure washer liquid dispenser
4. Apply to the areas that require cleaning and agitate with a broom or brush
5. Leave product on the surface up to 5 mins.
6. Apply water Agitate again and wash off using a hose or pressure washer.

Application Method 3 for when the Red Dirt is hard to remove using the dry method

1. Wash large deposits of dirt off the item being cleaned.
2. Mix AG Super Wash to required dilution rate in a bucket.
3. Apply the AG Super Wash using a hand spray bottle, directly to the area without wetting the area.
4. Work on a small area at a time.
5. Agitate the product using a non-scratch scourer or microfiber cloth in a circular motion, this will take some effort.
6. When you have completed and are happy with the result you will need to add water, hose or pressure cleaner to the desired area agitating the product with a sponge or microfiber cloth or the white non-scratch scourer
7. When moving to the next area to be cleaned the surface needs to be dry to get the best result with this dry method
8. If area still dirty you need to carry out the process again
9. Recommend giving the vehicle a complete wash after carrying out the Dry method so all the contaminates are removed to avoid streaking
10. Chamois Dry

Please Note**

Outback AG Super Wash is an environmentally sustainable non Dangerous goods product. Its formulated with the end-user and the environment in mind. You might need to scrub a little harder for your initial wash, but you will do so in a safe environment.